


Rig 6

Layout and Specifications



Drilling Services



RIG.

Carrier Self-propelled tandem drive
 Deck Engine 6V92
 Derrick 17.4 m; 62,000 DaN
 Tubulars Range III capacity
 Hydraulic Top Drive 8,000 foot pounds at 165 RPM
 Fuel Capacity Day tank
 Depth Rating 1,700 m

SUBSTRUCTURE

Dimensions 16.25 m X 3.61 m
 Lift Hydraulic ramp
 Hydraulic Lift Arm . Drill pipe & collars to 275 mm
 Kelly Bushing 4.25 m

BLOWOUT PREVENTERS - CLASS III

Annular Type . . . Townsend 84 7 1/16"; 21000 kPa
 Single Gates (2) Townsend 88 7 1/16"; 21000 kPa
 NACE Trimmed Yes

HYDRAULIC PIPE TUBS

Number 2
 Catwalk Yes
 Pipe Racks 2 sets

MUD PUMP

Type NCE D-375
 Rated 375 HP
 Liner 140 mm
 Stoke 356 mm
 Fuel Day tank

MUD TANK

Capacity 40 m³
 Shale Shaker DFT 500 B-2 linear
 Mud Mixing Centrifugal mission pump
 BOP Manifold 75 mm X 50 mm; 21,000 kPa

DRILL PIPE (UPSET)

Joints 155
 Size 102 mm
 Length Range II
 Connections 3 1/2" XH

DRILL COLLARS

Joints 5
 Size 121 mm
 Length Range II
 Connections 3 1/2" IF

COMBINATION BUILDING

Water 35 m³
 Fuel Day tank
 Change House Yes
 Light Plant 200 KW generator
 Accumulator ECS 4 station 300 liter

DOG HOUSE

Capacity 14,000 liters fuel

MOUNTED AIR COMPRESSOR

Equipped No

BOILER

Horse Power 80
 Water 16 m³
 Fuel Day tank

TOOL PUSH SHACK

Size 3 m wide X 13.68 m length

LOADS

Summer 9
 Winter 10

COMPLETIONS

DRILLING

PRODUCTION

RENTALS